



BLASTBLOCK SOUNDPROOFING

BlastBlock, the high-performance noise insulation material that uses very little space but has incredible noise reduction capabilities. BlastBlock, Noise Stopper, Blocks Acoustic Noise, Improved Transmission Loss All-in-one: Noise control, noise insulation, noise abatement., soundproofing.

blast-block.com

BA890

BLASTSEALANT
SOUNDPROOFING
SEALANT



BA890

BLASTSEALANT SOUNDPROOFING SEALANT

BlastBlock Acoustic Sound Sealant BA 890 is designed to seal gap around aluminum door and window frame with wall panel, fiber Cement sheet, pvc siding trim, MDF, plywood, furniture build in, ceiling, wall Crack. Non toxic, low odor and paintable. Anti fungus and bacteria protection On film. Many shade colours such as beech, teak, red oak, cherry, golden teak, Maple, orange brick, beige, ivory, light blue, walnut etc.,

BA890 contains low volatile organic compounds (VOCs) by using water as carrier instead of petroleum-based solvents which reduced levels of volatile organic compound (VOCs) that emit smog-forming chemicals pollutions into air and toxic harmful to humans especially reduce the incidence of eye or respiratory irritation from exposure to VOC fumes.

SPECIFICATION

Colours	White and special colours
Odor	Mild Acrylic
Specific gravity	1.69
PH	8.2-9.0
% solid	>84%
%Shrinkage	Less than 25%
Tack-free time	< 1 hour at room temperature
Extrudability / Stability	10 gms / sec
Rheology (slump)	0.05 inches.
Staining	0
Artificial weathering	Excellent
Extension/recovery, adhesion	90%
Full cure	72 hours
Flash Point	> 200°C F (94°C)
Water resistance	Excellent
Coverage	50-55 linear feet (3/8" bead)
Application temperature	5°C to 40°C
Shelf Life	1 year unopened at 30°C
Toxic	none



CAUTION! Do not use internally. Keep from freezing and sunlight.
 KEEP OUT OF REACH OF CHILDREN