



BLASTBLOCK SOUNDPROOFING

BlastBlock, the high-performance noise insulation material that uses very little space but has incredible noise reduction capabilities. BlastBlock, Noise Stopper, Blocks Acoustic Noise, Improved Transmission Loss All-in-one: Noise control, noise insulation, noise abatement., soundproofing.

blast-block.com



BA990

BLASTADHESIVE
SOUNDPROOFING
ADHESIVE

BA990

BLASTADHESIVE SOUNDPROOFING ADHESIVE

APPLICATIONS

Roof, Gutter, Chimney flashing, Skylight, Downspout, Cold Room, Plumbing, Heating, Ventilation and Air Conditioning

SPECIFICATION

Extrusion – Viscosity	6± 1 Grams / 15 Seconds (Semco@30 psi)
Weight per gallon	11.5 ± 0,25 lbs.
% Solids (TNV)	81.0 ± 2%
Colours	White, Grey, Brown and Black
Odor	Solvent
Shrinkage	Less than 20%
Application Temperature Range	Greater than 2°C
Tack – Free Time	2 Hours
Full Cure	7 Days
Paint Over time (Latex & Oil – based)	Latex : 12-24 Hours Oil – based after full cure
Flash Point	Greater than (38°C) – Combustible
Freeze thaw stability	Excellent
Stain Resistance	Passes 3 cycles
Slump Resistance	Excellent
Water Resistance	Excellent
Clean – up solvent (before cure)	Mineral spirits or paint thinner
Coverage	50 – 55 Linear Feet (3/8-Bead)
Service temperature range	-40°C to 107°C
Shelf life	1 year unopened (25°C)



CAUTION! Do not use internally. Keep from freezing and sunlight.
 KEEP OUT OF REACH OF CHILDREN