



Noise-Lock® STC 64 Steel Acoustic Door

DATASHEET

iac-acoustics-thailand.com

MAKING
THE
WORLD

A QUIETER
PLACE



Data Sheet

Noise-Lock® STC 64 Steel Acoustic Door



Overview

- Certified performance rating
- Manufactured to standard and custom sizes
- Available as single leaf or double door sets with glazing options
- Cam-lift hinges used to maximize acoustic seal
- Rugged steel construction
- Factory assembled and checked
- Finished in polyester powder coating as standard
- Wood veneer and powder coat finish options available
- Door leaf is 5" thick

Acoustic Rating

STC 64 (dB) to achieve minimum NIC 59 once installed (subject to flanking).

Rw (C; Ctr) 63 (-2 ; -9) dB to achieve minimum R'w 58 dB once installed (subject to flanking). Certified laboratory performance in single leaf arrangement as follows:

Frequency (Hz)	63	80	100	125	160	200	250	315	400	500	630	800	1000	1250	1600	2000	2500	3150	4000
Noise-Lock® STC 64	24	32	33	44	51	53	58	58	59	62	63	63	65	66	65	66	67	70	70

Standard Features



Acoustic Rated



Easy Access
Flat Thresholds

Optional Extras



Blast Resistance



RF Shielding



Fire Rated



Overview

IAC Acoustics produces an engineered system — fully factory assembled complete with a leaf, architectural split-frame, acoustic seals, cam-lift hinges and hardware. All doors are pre-hung for operational alignment, fit and finish before shipping.

Noise-Lock® doors are laboratory-tested for performance in independent laboratories, further supported by installed site testing. IAC Acoustics is renowned for quality, durability and guarantees in-field performance.

Hardware

IAC Acoustics Noise-Lock® doors are available with a number of standard and custom hardware options. Please contact your local IAC Acoustics office for further details.

The relationship between the clear and structural openings for both width and height is the same for all sizes of Noise-Lock® STC 64 doors. An example for a 3' x 7' door can be found in the table below:




Door Opening	Width (X)	Height (Y)
Structural/Rough Opening	3'-8 1/4"	7'-4 3/8"*
Clear Opening	3'	7'

* includes 1/4" threshold

Performance Features

- Self-aligning magnetic seals assure long life and high in-field performance, even under constant use
- Cam-lift hinges lower and seal the door to the floor eliminating the high maintenance of automatic drop seals
- Split frames eliminate in-field grouting to achieve the specified acoustic performance with quick and clean installation

- ① Acoustic Seal
- ② Cam-lift Hinge
- ③ Boot Seal
- ④ Sill
- ⑤ Male Frame
- ⑥ Main Frame / Female Frame





IAC Acoustics Thailand Co., Ltd.

6/54-56, Thanon Poemsin Soi 42,

Ongern - Sai Mai Bangkok 10220 Thailand

Ph: (+66) 02-1012827 | Email: info@iac-acoustics-thailand.com

iac-acoustics-thailand.com

IAC has worldwide offices and manufacturing plants in the UK, Australia, Canada, China, Malaysia, Indonesia, Thailand, Philippines Denmark, France, Germany, Italy, Spain, UAE - Dubai, USA Houston, USA Lincoln, USA - New York.

